

# SW3

**IEC-61850 L2/L3 PTP  
Ethernet Switch for  
Electrical Substations**



The **SW3** is a Gigabit / Fast **Ethernet Switch** specially designed to perform **Switching Functions** (L2 model) and **IPv4 Routing Functions** (L3 model)

The **SW3** Ethernet switch is also designed to meet the standards IEC 61850-3 and IEEE 1613 for the automation of electrical substations.

The **SW3** is a highly flexible device that allows different number and type of ports to be selected.

The **SW3** supports standard IEEE 1588v2 Clock Synchronization (Precision Time Protocol).

The **SW3** can be managed locally and remotely, through a local console, Telnet server and SSH server, or through a built-in web server (HTTP/HTTPS).

The SW3 supports the **SNMPv1**, **SNMPv2c** and **SNMPv3** management protocols, as well as other protocols and services such as **GARP/GMRP**, **LLDP**, **IGMP**, **DHCP**, **NTP/SNTP**, **TACACS+** and **RADIUS**. L3 model also supports the **RIPv1**, **RIPv2**, **OSPFv2** and **BGPv4** routing protocols, and the **VRRP** redundancy protocol.

The **SW3** not only complies with the STP and RSTP protocols for resolving loops in the network and operation in rings, but it also exceeds the recovery times obtained through said protocols.

## Main Applications

**Level 2** capabilities enable deployment of big scale LANs when the main requirements are: port density, switching performance, and logical complexity.

**Level 3** capabilities offer routing functionality between two or more configured VLANs, with each VLAN being made up of a set of local ports (Ethernet and Gigabit Ethernet).

## Equipment Interfaces

- ✓ 1 service console (DCE mode).
- ✓ 1 I/O connector.
- ✓ 4 front or rear Gigabit Ethernet SFP bays (copper and fiber).
- ✓ Up to 32 front or rear Fast Ethernet ports type 10/100Base-Tx (RJ-45), 100Base-Fx (MT-RJ, ST, SC and LC) and 100Base-Lx (LC SM) or Up to 24 front or rear IEEE 1588 (Precise Time Protocol) ports.
- ✓ Redundant power supply.
- ✓ Up to 8 electrical PoE ports (4 & 4).

## Main Facilities

**Full Duplex Wired Speed** switching core. Port speed automatic detection. STP and RSTP. Multiple VLANs management (250 simultaneously). QoS. Broadcast and Multicast traffic limitation. MAC access control lists and 802.1x user authentication. Q-in-Q operation (double-tagged). Link aggregation by LAG function (static). Port mirroring. Links in VLAN Native mode. Interoperability with IEDs that complies with IEC 61850. Traffic filtering (ACL) and firewall (L3 only).

**Compatible with standard IEEE 1588v2 Clock Synchronization** (Precision Time Protocol) in Transparent Clock (TC) P2P mode.

**L3 Routing Protocols** (RIPv1, RIPv2, OSPFv2, BGPv4).

## Management System

- HTTP graphical web-based, SSL.
- SNMP v1, v2c, v3.
- Telnet, VT100, SSH.
- Command Line Interface (CLI).
- RSA Key Management.
- Authentication and Accounting - TACACS+ (encrypted), RADIUS client.
- TLS 1.2.

## Additional Services

- LLDP.
- GARP/GMRP.
- IGMP.
- DHCP (L3 only).
- NTP/SNTP.
- VRRP (L3 only).

## Technical Information

### Fast Ethernet ports

Up to 32 ports resulting from:

- ✓ 8, 16, 24 or 32 ports 10/100Base-Tx (RJ-45). Up to 8 PoE ports (4 & 4)
- ✓ 4, 8, 12, 16, 20 or 24 ports 100Base-Fx MM (MT-RJ)
- ✓ 2, 4, 6, 8, 10, 12, 14 or 16 ports 100Base-Fx MM (ST or SC)
- ✓ 4, 8, 12, 16, 20 or 24 ports 100Base-Fx MM (LC)
- ✓ 4, 8, 12, 16, 20 or 24 ports 100Base-Lx SM (LC SM)

### IEEE 1588 (PTP) ports

Up to 24 ports resulting from:

- ✓ 6 ports 10/100Base-Tx (RJ-45)
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 Gigabit Ethernet SFP bays
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 ports 100Base-Fx MM (MT-RJ)
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 ports 100Base-Fx MM (LC)
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 ports 100Base-Lx SM (LC SM)
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 ports 100Base-Fx MM (ST)
- ✓ 4 ports 10/100Base-Tx (RJ-45) & 2 ports 100Base-Fx MM (SC)

### Service Port

- ✓ DB9 female connector in DCE mode. Speed of 115200 bit/s

### Mounting

Stand-alone (19"/1 s.u. chassis)

Dimensions: Height: 44 mm; Width: 440 mm; Depth: 287 mm; Weight: 3.4 kg

### Power Supply

36-72V<sub>DC</sub> (48V<sub>DC</sub> nominal) or multirange (80-360V<sub>DC</sub>, 80-260V<sub>AC</sub>)

Maximum consumption at 48 V<sub>DC</sub>: 40 W

Redundant power-supply option

### Temperature Range

From -25° C to +70° C

### Material

Grey (RAL 7024) zinc-plating iron

### EMI Immunity & Environment Compliance

IEC 61850-3

IEEE 1613

IEC 61000-6-5



Options of physical ports (Fast Ethernet or PTP)

